

ZETA TYRES

2021

PRODUCTS MANUAL

CHOOSE ZETA AND TAKE CONTROL

MADE IN THAILAND

www.zeta-tyres.com



HOW TO SELECT A TYRE

- Consult Vehicle Owner's Manual or Door Placard for Proper Tyre Size and Load/Speed Index
- Consider Average Vehicle Usage (Extended Highway Use, Off-Road, etc.)

MOUNTING/DISMOUNTING/SERVICE:

- Only Allow Trained Professionals to Mount, Dismount, or Service Your Tyres.

TYRE PRESSURE

- Consult Vehicle Owner's Manual or Door Placard for Proper Pressure for Your Vehicle. PSI/kg Indicted on Sidewall is the Maximum for the Tyre, Which May Not Be Proper for Your Vehicle.
- Check/Adjust Pressure when Tyres Are Cold.

CHECK THE FOLLOWING ITEMS MONTHLY

- TREAD AREA:
Uneven Wear, Cuts, Bulges, Foreign Objects
- SIDEWALL:
Ozone Cracking, Cuts, Bulges, Impact Damage

IF ANY OF THESE CONDITIONS EXIST - COSULT A PROFESSIONAL IMMEDIATLEY.



DISTRIBUTED BY

www.sd-international.com

These data can be changed by the manufacturer without prior notice and differently applied by regions.



THE BEST CHOICE
A BETTER WAY FORWARD

WHY ZETA

Looking for a tyre that is not made in China?
But one that can still be sourced at competitive prices.
But without compromising quality and performance?

Introducing Zeta,
the new premium tyre manufactured in Thailand.

Regardless of weather and road conditions, Zeta is the perfect choice for your driving needs.

With a variety of performance designs engineered in the USA, you will not be disappointed.

Zeta – the only tyre that fits your unique driving demands.

Choose Zeta and take control.

PRODUCTS



VERDANT



MEGLIO



ETALON



IMPERO



IMPERO A/T



CONSENSO H/T



IMPERO M/T



VERDANT



- An advanced tread design coupled with a high stylized sidewall design offers excellent driving comfort.
- Silica compound provides improved dry & wet traction along with lower rolling resistance.
- Equilibrium polyester body ply, wider steel belts plus high density jointless nylon full cover minimize tyre deformation, enhance durability and stability.



Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
185/70R14	88H	500AA	7.8	9.8	560	1235	210	130	300	44	44
195/70R14	91H	500AA	8.0	10.1	615	1356	210	130	300	44	44
205/70R15	96H	500AA	8.0	10.1	710	1565	210	130	300	44	44
215/70R15	98H	500AA	8.3	10.5	750	1653	210	130	300	44	44
165/65R14	79H	500AA	7.8	9.8	437	963	210	130	300	44	44
175/65R14	84T XL	500AA	7.8	9.8	500	1102	190	118	340	49	49
185/65R14	86H	500AA	7.8	9.8	530	1168	210	130	300	44	44
175/65R15	88H XL	500AA	7.8	9.8	560	1235	210	130	340	49	49
185/65R15	88H	500AA	7.8	9.8	560	1235	210	130	300	44	44
195/65R15	91V	500AA	8.0	10.1	615	1356	240	149	300	44	44
205/65R15	94H	500AA	8.0	10.1	670	1477	210	130	300	44	44
205/65R16	95V	500AA	7.8	9.8	690	1521	240	149	300	44	44
215/65R16	98H	500AA	8.0	10.1	750	1653	210	130	300	44	44

Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
185/60R14	82H	500AA	7.8	9.8	475	1047	210	130	300	44	44
195/60R14	86H	500AA	8.0	10.1	530	1168	210	130	300	44	44
165/60R15	77H	500AA	7.8	9.8	412	908	210	130	300	44	44
185/60R15	88H XL	500AA	7.8	9.8	560	1235	210	130	340	49	49
195/60R15	88V	500AA	8.0	10.1	560	1235	240	149	300	44	44
205/60R15	91V	500AA	8.0	10.1	615	1356	240	149	300	44	44
205/60R16	92V	500AA	8.0	10.1	630	1389	240	149	300	44	44
215/60R16	95V	500AA	8.3	10.5	690	1521	240	149	300	44	44
225/60R16	98H	500AA	8.3	10.5	750	1653	210	130	300	44	44
165/55R14	72H	500AA	7.8	9.8	355	783	210	130	300	44	44
185/55R15	82V	500AA	7.8	9.8	475	1047	240	149	300	44	44
195/55R15	85V	500AA	8.0	10.1	515	1135	240	149	300	44	44
205/55R16	91V	500AA	8.0	10.1	615	1356	240	149	300	44	44
215/55R16	97V XL	500AA	8.0	10.1	730	1609	240	149	340	49	49
225/55ZR16	99W XL	500AA	8.0	10.1	775	1709	270	168	340	49	49
195/50R15	82V	500AA	8.0	10.1	475	1047	240	149	300	44	44
205/50ZR16	87W	500AA	8.0	10.1	545	1201	270	168	300	44	44
205/45ZR16	87W XL	500AA	8.0	10.1	545	1201	270	168	340	49	49



MEGLIO



- Four wide straight grooves provide efficient drainage in wet conditions for improved vehicle stability.
- A straight rib block design applied to the outside of the tyre contact patch helps to eliminate unwanted road noise and increase cornering grip and driving stability.
- The Ultra-high performance design offers drivers impressive grip in dry and wet conditions, while multiple 2D kerfs and carving edges provide improved winter traction.



Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity	Max.Speed	Cold Infl. Press
						kg lbs	Km/h mph	Kpa psi
225/60R18	104V XL	500AA	8.0	10.1	900	1984	240 149	340 49
215/55ZR17	98W XL	500AA	8.0	10.1	750	1653	270 168	340 49
225/55ZR17	101W XL	500AA	8.0	10.1	825	1819	270 168	340 49
235/55ZR17	99W	500AA	8.3	10.5	775	1709	270 168	300 44
225/55ZR18	102W XL	500AA	8.0	10.1	850	1874	270 168	340 49
225/50ZR16	92W	500AA	8.0	10.1	630	1389	270 168	300 44
205/50ZR17	93W XL	500AA	8.0	10.1	650	1433	270 168	340 49
215/50ZR17	95W XL	500AA	8.0	10.1	690	1521	270 168	340 49
225/50ZR17	98W XL	500AA	8.0	10.1	750	1653	270 168	340 49
225/50ZR18	99W XL	500AA	8.0	10.1	775	1709	270 168	340 49
235/50ZR18	101W XL	500AA	8.0	10.1	825	1819	270 168	340 49
205/45ZR17	88 W XL	500AA	8.0	10.1	560	1235	270 168	340 49
215/45ZR17	91W XL	500AA	8.0	10.1	615	1356	270 168	340 49

Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity	Max.Speed	Cold Infl. Press
						kg lbs	Km/h mph	Kpa psi
225/45ZR17	94W XL	500AA	8.0	10.1	670	1477	270 168	340 49
235/45ZR17	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49
245/45ZR17	99W XL	500AA	8.0	10.1	775	1709	270 168	340 49
215/45ZR18	93W XL	500AA	8.0	10.1	650	1433	270 168	340 49
225/45ZR18	95W XL	500AA	8.0	10.1	690	1521	270 168	340 49
235/45ZR18	98W XL	500AA	8.0	10.1	750	1653	270 168	340 49
245/45ZR18	100W XL	500AA	8.0	10.1	800	1764	270 168	340 49
245/45ZR19	102W XL	500AA	8.0	10.1	850	1874	270 168	340 49
205/40ZR17	84W XL	500AA	8.0	10.1	500	1102	270 168	340 49
215/40ZR18	89W XL	500AA	8.0	10.1	580	1279	270 168	340 49
225/40ZR18	92W XL	500AA	8.0	10.1	630	1389	270 168	340 49
235/40ZR18	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49
245/40ZR18	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49
245/40ZR19	98W XL	500AA	8.0	10.1	750	1653	270 168	340 49
265/35ZR18	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49
245/35ZR19	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49
225/35ZR20	93W XL	500AA	8.0	10.1	650	1433	270 168	340 49
245/35ZR20	95W XL	500AA	8.0	10.1	690	1521	270 168	340 49
255/35ZR20	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49
275/30ZR20	97W XL	500AA	8.0	10.1	730	1609	270 168	340 49

ETALON



- Etalon gives you the all weather handling you need for your crossover vehicle, while delivering a comfortable and quiet ride.
- Circumferential zigzag grooves resist hydroplaning by channeling water away from the tread grooves.
- Optimized tread profile design reduces rolling resistance heavily and increases fuel efficiency.
- Integrated shoulder minimizes road noise and uneven wear for quite ride.



IMPERO




- 4 wide longitudinal grooves improves drainage performance.
- Anti-hydroplaning lateral grooves offers excellent wet performance.
- 3 center block provide straight-driving stability.
- Optimized shoulder blocks maximize grip during cornering.



Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed		Cold Infl. Press	
			mm	32nds	kg	lbs	Km/h	mph	Kpa	psi
235/75R15	105H	500AA	8.3	10.5	925	2039	210	130	300	44
215/70R16	100H	500AA	8.0	10.1	800	1764	210	130	300	44
225/70R16	103H	500AA	8.0	10.1	875	1929	210	130	300	44
235/70R16	106H	500AA	8.0	10.1	950	2094	210	130	300	44
245/70R16	111T XL	500AA	8.0	10.1	1090	2403	190	118	340	49
255/70R16	111T	500AA	8.3	10.5	1090	2403	190	118	300	44
265/70R16	112T	500AA	8.3	10.5	1120	2469	190	118	300	44
245/70R17	100T	500AA	8.3	10.5	800	1764	190	118	300	44
265/70R17	115S	500AA	8.3	10.5	1215	2679	180	112	300	44
235/65R16	103H	500AA	8.0	10.1	875	1929	210	130	300	44
215/65R17	99H	500AA	8.0	10.1	775	1709	210	130	300	44
225/65R17	102H	500AA	8.0	10.1	850	1875	210	130	300	44
235/65R17	108V XL	500AA	8.0	10.1	1000	2205	240	149	340	49
245/65R17	111H XL	500AA	8.0	10.1	1090	2406	210	130	340	49
235/65R18	110H XL	500AA	8.0	10.1	1060	2337	210	130	340	49
265/65R18	114H	500AA	8.0	10.1	1180	2601	210	130	300	44
275/65R18	116H	500AA	8.0	10.1	1250	2756	210	130	300	44
225/60R17	99V	500AA	8.3	10.5	775	1709	240	149	300	44
235/60R17	103S XL	500AA	8.3	10.5	875	1929	180	112	340	49
235/60R18	107V XL	500AA	8.0	10.1	975	2149	240	149	340	49
265/60R18	110V	500AA	8.0	10.1	1060	2337	240	149	300	44
235/55R18	100V	500AA	8.0	10.1	800	1764	240	149	300	44
255/55R18	109V XL	500AA	8.0	10.1	1030	2271	240	149	340	49

Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed		Cold Infl. Press	
			mm	32nds	kg	lbs	Km/h	mph	Kpa	psi
275/55ZR20	117W XL	500AA	8.3	10.5	1285	2833	270	168	340	49
245/45ZR20	103W XL	500AA	8.0	10.1	875	1929	270	168	340	49
275/45R20	110V XL	500AA	8.3	10.5	1060	2337	240	149	340	49
285/45R22	114V XL	500AA	8.3	10.5	1180	2601	240	149	340	49
305/45R22	118V XL	500AA	8.3	10.5	1320	2910	240	149	340	49
275/40ZR20	106W XL	500AA	8.3	10.5	950	2094	270	168	340	49
305/40R22	114V XL	500AA	8.3	10.5	1180	2601	240	149	340	49
265/40ZR22	106W XL	500AA	8.3	10.5	950	2094	270	168	340	49
265/35ZR22	102W XL	500AA	8.0	10.1	850	1875	270	168	340	49
295/35R24	110V XL	500AA	8.0	10.1	1060	2337	240	149	340	49
305/35ZR24	112W XL	500AA	8.3	10.5	1120	2469	270	168	340	49
315/35ZR20	110W XL	500AA	8.3	10.5	1060	2337	270	168	340	49
235/30ZR22	90W XL	500AA	8.3	10.5	600	1323	270	168	340	49
245/30ZR22	95W XL	500AA	8.0	10.1	690	1521	270	168	340	49
255/30ZR24	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49

IMPERO A/T



- Wraparound tread gives tyres a rugged look and guards against cuts, bruises and impact breaks, affords outstanding traction especially in muddy or snowy conditions.
- Reinforced wide tread gauge helps to prevent internal damage from impacts sustained when off the road.
- Thick sidewall rubber gauge helps to minimize damage from off-road impact.
- Reinforced carcass and rubber gauge improved hill climbing and steering stability both on and off the road.



Size	LI/SI	UTQG	mm	TD 32nds	Load Capacity kg	lbs	DUAL LOAD kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
215/75R15	100T	600AA	9.6	12.1	800	1764	/	/	190	118	300	44
255/70R15	108S	600AA	10.4	13.1	1000	2205	/	/	180	112	300	44
265/70R15	112S	600AA	10.4	13.1	1120	2469	/	/	180	112	300	44
245/70R16	107H	600AA	10.4	13.1	975	2149	/	/	210	130	300	44
265/65R17	112T	600AA	10.4	13.1	1120	2469	/	/	190	118	300	44
31*10.50R15LT-6PR	109S	NA	12.8	16.1	1030	2271	/	/	180	112	350	50
35*12.50R20LT-12PR	126R	NA	12.2	15.4	1700	3750	/	/	170	106	550	80
33*12.50R22LT-12PR	123S	NA	12.2	15.4	1550	3415	/	/	170	106	550	80
35*12.50R22LT-12PR	126R	NA	12.2	15.4	1700	3750	/	/	170	106	550	80
LT215/85R16-10PR	115/112S	NA	11.2	14.1	1215	2680	1120	2470	180	112	550	80
LT235/85R16-10PR	120/116Q	NA	11.2	14.1	1380	3042	1260	2778	160	99	550	80
LT235/80R17-10PR	120/117S	NA	11.2	14.1	1400	3085	1285	2835	180	112	550	80
LT235/75R15-8PR	110/107S	NA	11.2	14.1	1060	2335	975	2150	180	112	450	65

Size	LI/SI	UTQG	mm	TD 32nds	Load Capacity kg	lbs	DUAL LOAD kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
LT225/75R16-10PR	115/112S	NA	11.2	14.1	1215	2680	1120	2470	180	112	550	80
LT245/75R16-10PR	120/116S	NA	12.8	16.1	1380	3042	1260	2778	180	112	550	80
LT265/75R16-10PR	123/120S	NA	12.8	16.1	1550	3415	1400	3085	180	112	550	80
LT285/75R16-10PR	126/123S	NA	13.7	17.3	1700	3750	1550	3145	180	112	550	80
LT245/75R17-10PR	121/118S	NA	12.8	16.1	1450	3195	1320	2910	180	112	550	80
LT235/70R16-6PR	104/101S	NA	10.9	13.7	900	1984	825	1819	180	112	350	50
LT265/70R16-10PR	121/118S	NA	12.5	15.7	1450	3195	1320	2910	180	112	550	80
LT245/70R17-10PR	119/116S	NA	12.8	16.1	1360	3000	1250	2755	180	112	550	80
LT265/70R17-10PR	121/118S	NA	12.8	16.1	1450	3195	1320	2910	180	112	550	80
LT285/70R17-10PR	121/118Q	NA	13.7	17.3	1450	3195	1320	2910	160	99	450	65
LT265/70R18-10PR	124/121S	NA	12.8	16.1	1600	3525	1450	3195	180	112	550	80
LT275/70R18-10PR	125/122S	NA	12.8	16.1	1650	3460	1500	3305	180	112	550	80
LT275/65R18-10PR	123/120S	NA	12.8	16.1	1550	3415	1400	3085	180	112	550	80
LT285/65R18-10PR	125/122R	NA	12.2	15.4	1650	3640	1500	3305	170	106	550	80
LT325/65R18-10PR	127/124S	NA	12.2	15.4	1750	3860	1600	3525	180	112	450	65
LT275/65R20-10PR	126/123S	NA	12.8	16.1	1700	3750	1550	3415	180	112	550	80
LT265/60R20-10PR	121/118S	NA	12.8	16.1	1450	3195	1320	2910	180	112	550	80
LT285/60R20-10PR	125/122S	NA	13.7	17.3	1650	3640	1500	3305	180	112	550	80
LT325/60R20-10PR	126/123S	NA	12.2	15.4	1700	3750	1550	3415	180	112	450	65
LT265/50R20-10PR	121/118S	NA	12.2	15.4	1450	3195	1320	2910	180	112	550	80
LT275/55R20-10PR	120/117S	NA	12.2	15.4	1400	3085	1285	2833	180	112	550	80
LT285/55R20-10PR	122/119S	NA	12.2	15.4	1500	3305	1360	3000	180	112	551	80
LT305/55R20-10PR	121/118S	NA	12.2	15.4	1450	3195	1320	2910	180	112	450	65

CONSENSO H/T



- 3D wave-patterned kerfs design used in tyres provide improved grip and handling performance by minimizing block movement when driving, heavily improved all season performance.
- Multi-depth lateral lugs provide improved performance in wet and snow conditions.
- 4 straight grooves channel provides sure-footed performance in both wet and dry conditions.
- High stiffness center block improves steering performance.
- Button elements sized for good snow and wet traction, yet interlocking geometry maintains rib stiffness for handling.



IMPERO M/T



- Specially designed tread block provide better grip in mud, sand and snow.
- Unique stone-Ejector grooves along with a rugged shoulder help to prevent damage from impact.
- Optimized void-to-rubber ratio provides excellent traction.
- Large surface area tread blocks provide increased grip.



Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity	DUAL LOAD	Max.Speed	Cold Infl. Press
						kg	lbs	Km/h	psi
LT215/85R16-10PR	115/112S	NA	9.9	12.5	1215	2680	1120 2470	180 112	550 80
LT235/85R16-10PR	120/116Q	NA	9.9	12.5	1380	3042	1260 2778	160 99	550 80
LT235/80R17-10PR	120/117Q	NA	9.9	12.5	1400	3085	1285 2835	160 99	550 80
LT225/75R16-10PR	115/112S	NA	9.9	12.5	1215	2680	1120 2470	180 112	550 80
LT245/75R16-10PR	120/116S	NA	10.7	13.5	1380	3042	1260 2778	180 112	550 80
LT265/75R16-10PR	123/120Q	NA	10.7	13.5	1550	3415	1400 3085	160 99	550 80
LT245/75R17-10PR	121/118Q	NA	10.7	13.5	1450	3195	1320 2910	160 99	550 80
LT245/70R17-10PR	119/116S	NA	10.7	13.5	1360	3000	1250 2755	180 112	550 80
LT265/70R17-10PR	121/118Q	NA	10.7	13.5	1450	3195	1320 2910	160 99	550 80
235/75R15	109H	500AA	8.2	10.3	1030	2271	/ /	210 130	340 49
215/70R16	100H	500AA	8.2	10.3	800	1764	/ /	210 130	300 44
225/70R16	103T	500AA	8.2	10.3	875	1929	/ /	190 118	300 44
235/70R16	106H	500AA	8.2	10.3	950	2094	/ /	210 130	300 44
245/70R16	107H	500AA	8.2	10.3	975	2149	/ /	210 130	300 44
255/70R16	111H	500AA	8.2	10.3	1090	2403	/ /	210 130	300 44
265/70R16	112H	500AA	8.2	10.3	1120	2469	/ /	210 130	300 44
275/60R20	114T	500AA	11.5	14.5	1180	2601	/ /	190 118	240 35
275/55R20	117H	500AA	11.5	14.5	1285	2833	/ /	210 130	340 49

Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity	DUAL LOAD	Max.Speed	Cold Infl. Press
						kg	lbs	Km/h	psi
33X12.50R15LT-6pr	108Q	NA	15.7	19.8	1000	2205	160 99	250 35	
33x12.50R18LT-10pr	118Q	NA	15.7	19.8	1320	2910	160 99	450 65	
33x12.50R20LT-10pr	114Q	NA	15.4	19.4	1180	2600	160 99	450 65	
35X12.50R15LT-6pr	113Q	NA	15.7	19.8	1150	2535	160 99	250 35	
35X12.50R17LT-10pr	121Q	NA	15.7	19.8	1450	3195	160 99	450 65	
35X12.50R18LT-10pr	123Q	NA	15.7	19.8	1550	3415	160 99	450 65	
35X12.50R20LT-10pr	121Q	NA	15.7	19.8	1450	3195	160 99	450 65	
LT285/65R18-10pr	125/122Q	NA	15.7	19.8	1650	3460	160 99	550 80	